HyPanel Pro Datasheet

New hassle-free smart control panel for your home

The akubela HyPanel Pro, a smart control panel with an Android 10 operating system. The ALL IN ONE design integrates smart intercom, ZigBee gateway and home automation, and is compatible with plentiful ecosystem. Minimalist exterior design, allowing users to enjoy a higher quality communication experience. Support infrared remote control function, intelligent control of traditional home appliances, to achieve a more outstanding smart home experience.

At a Glance

- 8-inch touchscreen
- Metal frame with a decorative strip available in various colors and textures
- Built in with 2 gang dry contact, a digital input
- Built in with multiple sensors
- Support infrared remote control
- Android 10 OS powered by a high-performance Qualcomm chip
- Intercom, ZigBee gateway, and smart home control panel in one device



Basic Information

Model Number: PG71N-KNX-EU

• KNX Power Supply: 21-30VDC

Rated Current: 12mA/21V

• AUX Power Supply: 21-30VDC

Rated Current: 420mA/24V, 340mA/30V

• Rated Power: 10W

Digital Input: 1 gang, 0-5VDC

• Dry Contact Output: 2 gang, 100~240VAC

Rated Current: 4A

• Wire Range: 0.75 ~ 1.6mm²(18 ~ 15AWG)

Operation System: Android 10

• RAM/ROM: 2GB/16GB

• Wi-Fi: IEEE802.11 b/g/n/ac, @2.4GHz/5GHz

• Bluetooth: Bluetooth 4.2

• Ethernet Port: 1×RJ45, 10/100Mbps adaptive

• ZigBee: ZigBee 3.0

• Zigbee Sub-Device Limit: 128

 IR Control Coverage: Horizontal 125°, vertical 125°, 6m

Microphone: Dual microphones, -38dBV

• Speaker: Single speaker, $6\Omega/1.8W$



Appearance

• Material: Metal

 Screen: 8" multi-touch screen, AF hydrophobic anti-pollution fingerprint proof coating

• Screen Resolution: 1280×800 pixels

• Screen Brightness: 310 cd/m²

Sensors Built In

• Proximity Sensor: 30 ~ 60cm

• Light Sensor: Low-level lux detection

• Temperature Sensor: ±1°C, range: -10°C ~ 50°C

Humidity Sensor: ±5%, range: 10% ~ 90%RH,
without condensation

Working Environment

• Environment: For indoor use only

 Working Humidity: 10% ~ 90%RH, without condensation

Working Temperature: -10°C ~ 50°C

• Storage Temperature: -20°C ~ 70°C

• IP Rating: IP20

Installation

• Installation: Wall flush mounting


• Flush Mounted Module: EU/UK standard

Product Dimension Diagram (mm)












1 FRONT VIEW



3 LEFT VIEW



4 BACK VIEW



Cakubela