

Poly EncorePro 715 USB-A Monoaural Headset TAA

- Active
- 783N5AA
- NG

Specifications

All Specs

Boom mic length (mm)	120 - 145 mm
Boom mic rotation	290°
Cable length	218 cm
Cartons per layer	6
Cartons per pallet	24
Color	Black
Compatibility	Compatible with PCs via USB Type-A cable or USB Type-A/C® adapter
Compatible Operating Systems	Windows 11; Windows 10; macOS
Connection type	Wired: USB Type-A, USB Type-A/C® adapter
Connects to	PC
Country of origin	Made in Mexico
ECCN	EAR99
Ecolabels	TCO Certified
Headphone type	On-ear (monaural)
HTS code	8518302000
Layers per pallet	4
Manufacturer product number	203476-01
Manufacturer Warranty	Poly standard two-year limited warranty
Material Type for item	FERT
Microphone bandwidth	100 Hz to 6.8 kHz
Microphone type	Noise cancelling

Multiple order quantity	48
Package dimensions (W x D x H)	149 x 175 x 55 mm
Package weight	190.68 g
Pallet dimensions (W x D x H)	101.6 x 121.9 x 127.3 cm
Pallet weight	20.11 kg
Products per pallet	648
Products per pallet layer	162
Registration required	No
Speaker bandwidth	150 Hz to 6.8 kHz
Speaker size	28 mm
UNSPSC code	43191638
Weight	53 g
What's in the box	Headset
Logistics	
ECCN	EAR99
HTS code	8518302000
What's in the box	Headset
Cable length	218 cm
Package dimensions (W x D x H)	149 x 175 x 55 mm
Pallet dimensions (W x D x H)	101.6 x 121.9 x 127.3 cm
Country of origin	Made in Mexico
Cartons per layer	6
Cartons per pallet	24
Multiple order quantity	48
Layers per pallet	4

Products per pallet	648
Products per pallet layer	162
Manufacturer product number	203476-01
Material Type for item	FERT
UNSPSC code	43191638
Package weight	190.68 g
Pallet weight	20.11 kg
Weight	53 g

Sustainability

Country of origin	Made in Mexico
-------------------	----------------

Specifications

[1] SoundGuard Digital Plantronics owns sophisticated algorithms including: Protects against Acoustic Shock by limiting sounds to below 118 dBA; G616 anti-startle protection that limits the noise level to below 102 dB SPL and is therefore compliant to the Australian Communications Industry Forum (ACIF) G616 recommendation; Average daily noise exposure measures and controls sound to prevent the average daily sounds exposure from exceeding 80 dBA or 85 dBA time-weighted average (TWA).

[2] Requires Poly Lens Desktop App to enable SoundGuard Digital features.

Legal disclaimer

[2] Available on QD models only.