

Poly EncorePro 525 USB-A Stereo Headset

- Active
- 783R3AA
- NG

Specifications

All Specs

Boom mic length (mm)	135 mm
Boom mic rotation	290°
Cable length	2085 mm
Cartons per layer	12
Cartons per pallet	96
Certified collaboration software	Zoom certified
Color	Black
Compatibility	Compatible with PCs via USB Type-A cable or USB Type-A/C® adapter
Compatible Operating Systems	Windows 11; Windows 10; macOS
Connection type	Wired: USB Type-A, USB Type-A/C® adapter
Connects to	PC
Country of origin	Made in Mexico
Dimensions (W x D x H)	11.1 x 14.9 x 6.7 cm
ECCN	EAR99
Ecolabels	TCO Certified
Headphone type	On-ear (stereo)
HTS code	8518302000
Indicator light	On call; On muted call
Layers per pallet	8
Manufacturer product number	218274-01
Manufacturer Warranty	Poly standard two-year limited warranty

Material Type for item	FERT
Microphone bandwidth	35 Hz to 21 kHz
Microphone type	Noise cancelling
Multiple order quantity	10
Package dimensions (W x D x H)	190 x 175 x 55 mm
Package weight	206.5 g
Pallet dimensions (W x D x H)	101.6 x 121.9 x 196.9 cm
Pallet weight	198.24 kg
Products per pallet	960
Products per pallet layer	120
Registration required	No
Sensitivity (microphone)	-40 +/-3 dB
Signal-to-noise ratio	>53 dB
Speaker bandwidth	20 Hz to 20 kHz
Speaker size	30 mm
UNSPSC code	43191638
Weight	74 g
What's in the box	Headset
Logistics	
ECCN	EAR99
HTS code	8518302000
What's in the box	Headset
Cable length	2085 mm
Package dimensions (W x D x H)	190 x 175 x 55 mm
Pallet dimensions (W x D x H)	101.6 x 121.9 x 196.9 cm

Dimensions (W x D x H)	11.1 x 14.9 x 6.7 cm
Country of origin	Made in Mexico
Cartons per layer	12
Cartons per pallet	96
Multiple order quantity	10
Layers per pallet	8
Products per pallet	960
Products per pallet layer	120
Manufacturer product number	218274-01
Material Type for item	FERT
UNSPSC code	43191638
Package weight	206.5 g
Pallet weight	198.24 kg
Weight	74 g

Sustainability

Country of origin	Made in Mexico
-------------------	----------------

Specifications

[1] SoundGuard Digital Plantronics owns sophisticated algorithms including: Protects against Acoustic Shock by limiting sounds to below 118 dBA; G616 anti-startle protection that limits the noise level to below 102 dB SPL and is therefore compliant to the Australian Communications Industry Forum (ACIF) G616 recommendation; Average daily noise exposure measures and controls sound to prevent the average daily sounds exposure from exceeding 80 dBA or 85 dBA time-weighted average (TWA).

[2] Requires Poly Lens Desktop App to enable SoundGuard Digital features.

[3] The functionality of your peripherals may vary based on your VDI vendor, UC application and OS. Please check with your application's website. Some examples are provided below: 1. Citrix: a. <https://docs.citrix.com/en-us/citrix-virtual-apps-desktops/multimedia/opt-ms-teams.html> b. <https://docs.citrix.com/en-us/citrix-virtual-apps-desktops/1912-ltsr/multimedia/opt-ms-teams.html> 2. Zoom: <https://support.zoom.us/hc/en-us/articles/360031441671-VDI-client-features-comparison> 3. Vmware: <https://kb.vmware.com/s/article/86475> 4. Igel: <https://kb.igel.com/igelos-11.08.330/en/poly-headsets-compatibility-with-igel-os-88018889.html>

Legal disclaimer

