

Poly DA85-M USB to QD Black Adapter TAA

Active

786C8AA

NG

Specifications

All Specs

Cable length	130 cm
Cartons per layer	12
Cartons per pallet	96
Compatibility	Compatible with any Poly Quick Disconnect headset
Connection type	USB Type-C*; USB Type-A
Country of origin	Made in China
Dimensions (W x D x H)	75 x 25 x 10 mm
Dimensions (W x D x H) Note	Inline module
ECCN	EAR99
HTS code	8471809000
Indicator light	On call (green/red/amber); On muted call (red)
Layers per pallet	8
Manufacturer product number	218268-01
Manufacturer Warranty	Poly standard two-year limited warranty
Material Type for item	FERT
Microphone bandwidth	150 Hz to 6.8 kHz
Multiple order quantity	40
Package dimensions (W x D x H)	150 x 90 x 27 mm
Package weight	71 g
Pallet dimensions (W x D x H)	101.6 x 121.9 x 196.9 cm
Pallet weight	130.17 kg

Products per pallet	3840
Products per pallet layer	480
Registration required	No
Tone controls	With button presses
UNSPSC code	26121630
Weight	30 g
What's in the box	Poly DA85-M Microsoft Teams Certified USB-A USB-C Quick Disconnect Adapter

Logistics

ECCN	EAR99
HTS code	8471809000
What's in the box	Poly DA85-M Microsoft Teams Certified USB-A USB-C Quick Disconnect Adapter
Cable length	130 cm
Dimensions (W x D x H) Note	Inline module
Package dimensions (W x D x H)	150 x 90 x 27 mm
Pallet dimensions (W x D x H)	101.6 x 121.9 x 196.9 cm
Dimensions (W x D x H)	75 x 25 x 10 mm
Country of origin	Made in China
Cartons per layer	12
Cartons per pallet	96
Multiple order quantity	40
Layers per pallet	8
Products per pallet	3840
Products per pallet layer	480
Manufacturer product number	218268-01
Material Type for item	FERT

UNSPSC code	26121630
Package weight	71 g
Pallet weight	130.17 kg
Weight	30 g

Specifications

[1] SoundGuard Digital Plantronics owns sophisticated algorithms including: Protects against Acoustic Shock by limiting sounds to below 118 dBA; G616 anti-startle protection that limits the noise level to below 102 dB SPL and is therefore compliant to the Australian Communications Industry Forum (ACIF) G616 recommendation; Average daily noise exposure measures and controls sound to prevent the average daily sounds exposure from exceeding 80 dBA or 85 dBA time-weighted average (TWA).

Legal disclaimer