

Poly OBi VVX 350 6-Line IP Phone and PoE-enabled

Discontinued

89B59AA

NI

Specifications

All Specs

Audio	Poly HD Voice; Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression; Poly Acoustic Fence technology eliminates background noise when using a handset or wired headset; Poly Computer Audio Connector app installed on your PC (Windows only) enables selecting your phone for PC audio in/out to use the phones handset, optional headset and handsfree speakerphone with PC applications; Individual volume settings with visual feedback for each audio path; Voice activity detection; Comfort noise generation; DTMF tone generation (RFC 2833 and in-band); Low delay audio packet transmission; Adaptive jitter buffers
Audio codecs	G.711 (A-law and μ -law); G.722; G.729AB; iLBC; OPUS
Cartons per layer	6
Cartons per pallet	42
Certifications and compliances	AS/NZS 60950-1; Australia RCM; Brazil ANATEL; CAN/CSA C22.2 No. 62368-1-14EN 60950-1; CE Mark; CISPR22 Class B; EN 60950-1 & EN 62368-1; EN55024; EN55032 Class B; EN61000-3-2, EN61000-3-3; FCC Part 15 (CFR 47) Class B; ICES-003 Class B; IEC 60950-1 & IEC 62368-1; NZ Telepermit; ROHS compliant; So. Korea KC; Saudi Arabia CITC; So. Africa ICASA; UAE TRA; UL 60950-1 and UL 62368-1; VCCI Class B; Indonesia SDPPI; Mexico NOM ANCE; Russia CU Mexico NOM ANCE;Russia CU;TAA
Color	Black
Country of origin	Made in China, Laos or Mexico
Display features	Digital picture frame
Display size (diagonal)	8.9 cm (3.5")
ECCN	5A992
Energy star certified	ENERGY STAR® certified
Headset and handset compatibility	Compatible with commercially available TTY adapter equipment; Compliant with ADA Section 508 Subpart B 1194.23 (all); Hearing aid compatibility to ITU-TP.370 and TIA 504A standards; Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids
Headset ports	1 RJ-9; 1 Electronic Hook Switch (EHS) port for optional adapter
HTS code	8517180020
Layers per pallet	7
Management Software	Poly Lens; Poly Zero Touch Provisioning; Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management; SDP
Manufacturer product number	2200-48832-025
Manufacturer Warranty	Poly standard one-year limited warranty
Material Type for item	FERT

Multiple order quantity	10
Native resolution	320 x 240
Network protocols, supported	10/100/1000 Base-TX across LAN and PC ports; Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment; Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation; Manual or dynamic host configuration protocol (DHCP) network setup
Operating humidity range	5 to 95%
Operating temperature range	0 to 40°C
Package dimensions (W x D x H)	23.3 x 26.2 x 6.2 cm
Package weight	300 g
Pallet dimensions (W x D x H)	101.6 x 121.9 x 149 cm
Pallet weight	357 kg
Panel technology	Color LCD
Ports	2 USB 2.0 Type-A (for media, storage applications, headset, optional Wi-Fi adapter); 2 RJ-45 (10/100/1000BASE-TX Mbps)
Power	Built-in auto sensing IEEE 802.3af Power over Ethernet (Class 0); 13 W (maximum)
Products per pallet	420
Products per pallet layer	60
Registration required	No
Security management	802.1X Authentication and EAPOL Media encryption via SRTP; Digest authentication; Encrypted configuration files; HTTPS secure provisioning; Password login; Support for signed software executables; Support for URL syntax with password; Transport Layer Security (TLS); SRTP media encryption using AES 256 bits
Special features	Adjustable desk stand (2 positions); Unicode UTF-8 character support
Storage temperature range	-40 to 70°C
Telephony and call handling features	Anonymous call indication; Block anonymous call; Busy Lamp Field (BLF); Call forward on busy, on no answer, unconditional; Call return; Distinctive incoming call treatment/call waiting; Do not disturb function; Repeat dialing; Shared call/bridged line appearance; Corporate directory; Call park/retrieve; Directed call pickup; Flexible line appearance (one or more line keys can be assigned for each line extension); Up to 6 SIP registrations per phone; Integrated IVR and Auto attendant; Up to 3-way locally mixed conference call; Call waiting; Maximum sessions control; External conference bridging; Visual voicemail support; XML Application Framework for third-party business and personal applications
UNSPSC code	43191511
VoIP features	24 lines (SIP registrations)
What's in the box	Console; Desk stand/wall mount hardware; Handset with handset cord; Network (LAN) cable-CAT-5E; Setup sheet

Logistics

ECCN	5A992
HTS code	8517180020
What's in the box	Console; Desk stand/wall mount hardware; Handset with handset cord; Network (LAN) cable-CAT-5E; Setup sheet
Package dimensions (W x D x H)	23.3 x 26.2 x 6.2 cm
Pallet dimensions (W x D x H)	101.6 x 121.9 x 149 cm
Country of origin	Made in China, Laos or Mexico
Cartons per layer	6
Cartons per pallet	42
Multiple order quantity	10
Layers per pallet	7
Products per pallet	420
Products per pallet layer	60
Manufacturer product number	2200-48832-025
Material Type for item	FERT
UNSPSC code	43191511
Package weight	300 g
Pallet weight	357 kg

Specifications

[1] Most software-enabled features must be supported by the service provider platform. Please contact your IP PBX/softswitch vendor or service provider for a list of supported features.

[2] Optional wall mount kit can be ordered separately.

[3] External universal AC/DC adapter, 5 VDC, 3 A, 15 W (sold separately).

Legal disclaimer