

Poly Savi 8245 DECT 1880-1900 MHz Headset +USB-A to USB-C Cable +D400

- Active
- 8D3H2AA
- NG

Specifications

All Specs

|                                  |                                                                                                        |
|----------------------------------|--------------------------------------------------------------------------------------------------------|
| Audio                            | Hybrid Active noise cancellation (ANC); Microphone noise cancellation with close conversation limiting |
| Battery life                     | Unlimited talk and standby time                                                                        |
| Battery type                     | Rechargeable Li-ion polymer                                                                            |
| Cartons per layer                | 12                                                                                                     |
| Cartons per pallet               | 72                                                                                                     |
| Certified collaboration software | Google Meet certified                                                                                  |
| Charge time                      | <3 hours                                                                                               |
| Charging type                    | Charge stand                                                                                           |
| Color                            | Black                                                                                                  |
| Compatibility                    | Compatible with PCs, desk phones and smartphones via DECT™, Bluetooth ® , USB Type-A or RJ-11 cable    |
| Compatible Operating Systems     | Windows 11; Windows 10; macOS; Android™; iOS                                                           |
| Connection type                  | Wireless: DECT™, USB Type-A D400, USB Type-A/C® adapter                                                |
| Connects to                      | Desk phone; PC; Mobile                                                                                 |
| Country of origin                | Made in Mexico                                                                                         |
| ECCN                             | 5A992                                                                                                  |
| Ecolabels                        | TCO Certified                                                                                          |
| End of Life CO2e (kg)            | 0.2                                                                                                    |
| HTS code                         | 8517620090                                                                                             |
| Impedance                        | 32 ohms                                                                                                |
| Indicator light                  | On call                                                                                                |
| Layers per pallet                | 6                                                                                                      |

|                               |                                                                                                     |
|-------------------------------|-----------------------------------------------------------------------------------------------------|
| Management Software           | Poly Lens                                                                                           |
| Manufacturer product number   | 211203                                                                                              |
| Manufacturer Warranty         | Poly standard two-year limited warranty                                                             |
| Material Type for item        | FERT                                                                                                |
| Microphone bandwidth          | 100 Hz to 10 kHz                                                                                    |
| Microphone type               | Noise cancelling                                                                                    |
| Multiple order quantity       | 5                                                                                                   |
| Package weight                | 300 g                                                                                               |
| Paired devices                | Up to 2                                                                                             |
| Pallet dimensions (W x D x H) | 101.6 x 121.9 x 149 cm                                                                              |
| Pallet weight                 | 357 kg                                                                                              |
| Production CO2e (kg)          | 9                                                                                                   |
| Products per pallet           | 360                                                                                                 |
| Products per pallet layer     | 60                                                                                                  |
| Registration required         | No                                                                                                  |
| Security                      | DECT™ security certified; AES 64 bits encryption                                                    |
| Sensitivity (microphone)      | 112 dB SPL                                                                                          |
| Speaker bandwidth             | 20 Hz to 20 kHz (multimedia mode); 100 Hz to 6.8 kHz (wideband mode)                                |
| Speaker size                  | 32 mm                                                                                               |
| Total CO2e (kg)               | 20                                                                                                  |
| Transportation CO2e (kg)      | 0.3                                                                                                 |
| UNSPSC code                   | 43191638                                                                                            |
| UPC number                    | (ABG) 197498519326; (UUF) 196548579365                                                              |
| Voice alerts                  | Volume maximum; Volume minimum; Mute on; Mute off; Muted; Connection status; Talk time; Battery low |
| Weight                        | 21 g                                                                                                |

What's in the box

Wireless headset; USB Type-A cable; USB Type-C  cable; Office base; AC power adapter; Telephone cable; Headband; Neckband; Kit with ear loops and earbuds; Charging cradle

Wireless range

Up to 180 m in open area; Up to 55 m in typical office environment

Logistics

ECCN

5A992

HTS code

8517620090

UPC number

(ABG) 197498519326; (UUF) 196548579365

What's in the box

Wireless headset; USB Type-A cable; USB Type-C  cable; Office base; AC power adapter; Telephone cable; Headband; Neckband; Kit with ear loops and earbuds; Charging cradle

Pallet dimensions (W x D x H)

101.6 x 121.9 x 149 cm

Country of origin

Made in Mexico

Cartons per layer

12

Cartons per pallet

72

Multiple order quantity

5

Layers per pallet

6

Products per pallet

360

Products per pallet layer

60

Manufacturer product number

211203

Material Type for item

FERT

UNSPSC code

43191638

Package weight

300 g

Pallet weight

357 kg

Weight

21 g

Sustainability

Country of origin

Made in Mexico

End of Life CO2e (kg)

0.2

|                          |     |
|--------------------------|-----|
| Energy Usage CO2e (kg)   | 8   |
| Production CO2e (kg)     | 9   |
| Total CO2e (kg)          | 20  |
| Transportation CO2e (kg) | 0.3 |

Specifications

[1] SoundGuard Digital Plantronics owns sophisticated algorithms including: Protects against Acoustic Shock by limiting sounds to below 118 dBA; G616 anti-startle protection that limits the noise level to below 102 dB SPL and is therefore compliant to the Australian Communications Industry Forum (ACIF) G616 recommendation; Average daily noise exposure measures and controls sound to prevent the average daily sounds exposure from exceeding 80 dBA or 85 dBA time-weighted average (TWA).

[2] Requires Poly Lens Desktop App to enable SoundGuard Digital features.

[3] Requires downloadable software on Poly.com/lens. Host PC requires Windows 10 or higher.

Legal disclaimer