

Poly Studio X52 All-In-One Video Bar No Power Cord GSA/TAA

- Active
- 8D8K5AA
- NJ

Specifications

All Specs

Audio	Full duplex audio; Acoustic echo cancellation; Poly NoiseBlockAI technology; Poly Acoustic Fence technology; Automatic gain control (AGC)
Audio standards	22 kHz with Polycom Siren 22 technology; 20 kHz with G.719 (M- Mode) and Polycom Siren 22 technology; 14 kHz with Polycom Siren 14 technology, G.722.1 Annex C; 7 kHz with G.722, G.722.1; 3.4 kHz with G.711, G.728, G.729A
Camera range (metric)	Up to 6.1 m
Camera resolution	2160p, 4K UHD (3840 x 2160)
Camera type	Single-lens
Cartons per layer	4
Cartons per pallet	28
Certified collaboration software	Microsoft Teams certified; Zoom certified; Google Meet certified
Color	Black
Content sharing	Apple AirPlay; Miracast; Digital Whiteboarding; HDMI input
Content video resolution (input)	UHD (3840 x 2160); HD (1920 x 1080); WSXGA+ (1680 x 1050); UXGA (1600 x 1200); SXGA (1280 x 1024); WXGA (1280 x 768); HD (1280 x 720); XGA (1024 x 768); SVGA (800 x 600)
Content video resolution (output)	UHD (3840 x 2160); HD (1920 x 1080); WSXGA+ (1680 x 1050); SXGA+ (1400 x 1050); SXGA (1280 x 1024); HD (1280 x 720); XGA (1024 x 768)
Country of origin	Made in Laos
Diagonal field of view (dFoV)	110°
Digital signage	Appspace; Raydiant
Dimensions (W x D x H)	769.5 x 115.2 x 103 mm
ECCN	5A992
Heat dissipation cooling	65 BTU/h
Horizontal field of view (hFoV)	95°
HTS code	8517620090
Interoperability	Google Meet, Microsoft Teams, Zoom certified; Support for native 3rd party applications including Dialpad, GoToRoom, RingCentral and StarLeaf; All cloud service providers through Poly Video App mode; USB Device mode

Layers per pallet	7
Lens cover capabilities	Attachable
Management Software	Poly Lens
Manufacturer product number	G7200-87620-125
Manufacturer Warranty	Poly standard one-year limited warranty
Material Type for item	FERT
Microphone pickup range (metric)	Up to 6.09 m
Microphone type	Two MEMS microphones; Two second-order microphones
Multiple order quantity	1
Network capabilities	IPv4; IPv6; 1x 10/100/1G Ethernet; Auto-MDIX; H.323 and/or SIP up to 6 Mbps in Poly App video mode; Polycom Lost Packet Recovery (LPR) technology; Dynamic bandwidth allocation; Reconfigurable MTU size; Web proxy support: basic, digest, and NTLM; Simple Certificate Enrollment Protocol (SCEP)
Non-Operating Humidity Range	5 to 95%
Non-operating temperature - Celsius	-40 to 70 °C
Operating altitude	4,877 m
Operating humidity range	15 to 80%
Operating temperature range	0 to 40 °C
Operating voltage	37 VA @ 120 V @ 60 Hz; 37 VA @ 230 V @ 50/60 Hz; 25 W (heavily loaded); 8 W (idle/sleep)
Pallet dimensions (W x D x H)	101.6 x 121.9 x 149 cm
Pallet weight	357 kg
People video resolution	4K, 30 fps (TX and RX) from 2048 Kbps; 1080p, 60 fps from 1740 Kbps; 1080p, 30 fps from 1024 Kbps; 720p, 60 fps from 832 Kbps; 720p, 30 fps from 512 Kbps
Physical security	Standard Kensington lock slot
Ports	1 HDMI-in 2.0 (video and audio); 2 HDMI-out 2.0 (video); 1 USB Type-C® 5Gbps signaling rate; 2 USB Type-A 5Gbps signaling rate; 1 RJ-45; 1 line in (optional microphone)
Power supply type	External; Auto sensing
Products per pallet	280
Products per pallet layer	40
Registration required	No

Security management	AES 128 bits encryption; AES 256 bits encryption; H.235.6 support; Authenticated access to admin menus, web interface, and APIs; Local account password policy configuration; Security profiles; Local account and login port lockout; Secure defaults; Remote logging with support for TLS; Active directory external authentication; Binary Floor Control Protocol (BFCP)
Sensitivity (speaker)	79 dB
Smart camera technology	People framing; Group framing; DirectorAI perimeter; Speaker framing
Speaker output power	2 x 20 W (RMS)
Speaker type	Dual speakers
Total camera resolution (megapixels)	20 MP
UNSPSC code	45111902
Video frame rate	30 fps
Video standards	H.264 AVC; H.264 High Profile; H.265; H.239
Weight	2.54 kg
What's in the box	Ethernet cable; Monitor clamp; AC power adapter; HDMI cable; Poly Studio X52
Wireless technologies	Wi-Fi 802.11a/b/g/n/ac/ax (MIMO) Multi-channel Concurrency
Zoom capability	5x digital
Logistics	
ECCN	5A992
HTS code	8517620090
What's in the box	Ethernet cable; Monitor clamp; AC power adapter; HDMI cable; Poly Studio X52
Pallet dimensions (W x D x H)	101.6 x 121.9 x 149 cm
Dimensions (W x D x H)	769.5 x 115.2 x 103 mm
Country of origin	Made in Laos
Cartons per layer	4
Cartons per pallet	28
Multiple order quantity	1
Layers per pallet	7

Products per pallet	280
Products per pallet layer	40
Manufacturer product number	G7200-87620-125
Material Type for item	FERT
UNSPSC code	45111902
Pallet weight	357 kg
Weight	2.54 kg

Sustainability

Country of origin	Made in Laos
-------------------	--------------

Specifications

[1] Requires downloadable software on Poly.com/lens. Host PC requires Windows 10 or higher.

[2] Not available on no radio versions.

Legal disclaimer